

# HURCO®

# TM8MYi



IMTS SHOW SPECIAL

~~\$129,995~~ **\$119,995**

WHILE  
SUPPLIES  
LAST

- » 4.33 inches of Y-axis travel.
- » 5,000-RPM live tools.
- » True slant-bed design promotes increased rigidity.
- » Linear roller bearing guideways promote rigidity and reduce vibration.
- » Renishaw swing-down tool setter.
- » Swing Over Bed: 19.29 in.
- » Swing Over Cross Slide: 19.29 in.
- » Maximum Turning Diameter: 12.60 in.
- » Travels (X, Z): 9.1 x 21.65 in.; 1,181 / 472 / 1,181 in./min.
- » Spindle:
  - Speed: 4,000 RPM
  - Power (continuous): 15.5 HP
  - Torque (continuous): 72.4 ft. lbs.
- » Tool Holder Type: BMT55
- » Rapid Traverse Rate: (X, Y, Z): 1,181 / 472 / 1,181 in./min.
- » Max. Programmable Feedrate (X, Y, Z): 1,181 / 472 / 1,181 in./min.

## Industry-Leading Control Specifications [Standard]



The Industry's  
Most Flexible  
Control

- \* Industry Standard NC
- \* Conversational
- \* NC/Conversational Merge

WinMax®

- » Up to 10,000-block lookahead with UltiMotion®
- » 128-GB Solid State Hard Drive
- » 4-GB RAM Memory
- » 2.7-GHz Dual Core Processor
- » Up to 4,000 bps Processing Speed
- » Ergonomically-designed control console with 19" LCD touch-screen.

**VISIT [HURCO.COM/WINMAX](http://HURCO.COM/WINMAX) TO LEARN MORE.**

# HURCO®

Hurco Companies, Inc. | One Technology Way | Indianapolis, IN 46268 | 800.634.2416 | [info@hurco.com](mailto:info@hurco.com) | [HURCO.com](http://HURCO.com)

Machines shown with options. Information may change without notice. Optimum machine performance is reliant upon installation conditions at the facility, such as power supply, air supply, and ambient air conditions.